

SERVO[®] PRODUCT DATA SHEET

SERVO GEAR SUPER 85W-140



GRADES AVAILABLE - SERVO GEAR SUPER 85W-140

DESCRIPTION

Servo Gear Super 85W-140 oil is an extreme pressure automotive gear lubricant. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure, anti-rust-corrosion characteristics.

APPLICATION

Servo Gear Super 85W-140 oil is recommended for passenger car, bus and highway truck hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.

PERFORMANCE BENEFITS

- Satisfy the lubrication requirements of a wide variety of gears.
- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability.
- Provide good protection against corrosion.

PERFORMANCE STANDARDS

Servo Gear Super 85W-140 meets

- API Service GL 5
- US military MIL-L-2105

CHARACTERISTICS

SAE GRADE	85W-140
Kinematic Viscosity cSt @ 100°C	28 – 32
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 18

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

