

# SERVO SYNCHRO 80W-90

## GRADES AVAILABLE - SERVO SYNCHRO 80W-90

<p><b>DESCRIPTION</b></p> <p>Servo Synchro is extreme pressure automotive gear oil. This oil is blended from selected base stocks and contain special additives to provide extreme pressure characteristics for wear protection.</p>	<p><b>APPLICATION</b></p> <p>Servo Synchro oil is recommended for synchromesh gear box and transfer case of light, medium and heavy commercial vehicles like bus, trucks, etc.</p>
<p><b>PERFORMANCE BENEFITS</b></p> <p>Servo Synchro</p> <ul style="list-style-type: none"> <li>• Provide protection against wear, due to good EP characteristics</li> <li>• Give long service life even under high temperature operation since it has excellent oxidation stability</li> <li>• Provide good protection against corrosion.</li> <li>• Extended oil drain interval.</li> </ul>	<p><b>PERFORMANCE STANDARDS</b></p> <p>Servo Synchro meets:</p> <ul style="list-style-type: none"> <li>• API Service GL 4</li> </ul>

## CHARACTERISTICS

SAE GRADE	80W-90
Kinematic Viscosity cSt @ 100°C	14 –16
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 27
Copper Corrosion @ 121°C, 1 hr, Max	1

## HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) OR [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

