



## SERVO GEAR ALT 140

### GRADES AVAILABLE - SERVO GEAR ALT 140

#### DESCRIPTION

Servo Gear ALT 140 oil is an extreme pressure automotive gear lubricant. This oil is blended from selected base stocks and contain additives to provide extreme pressure, anti-rust-corrosion characteristics.

#### APPLICATION

Servo Gear ALT 140 oil is recommended for Ashok Leyland commercial vehicles with spiral-bevel type rear axles.

#### PERFORMANCE BENEFITS

Servo Gear ALT 140 oil

- Satisfy the lubrication requirements of a wide variety of gears.
- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability
- Provide good protection against corrosion

#### PERFORMANCE STANDARDS

Servo Gear ALT 140 oil meets:

- API Service GL 4

#### APPROVAL

- Ashok Leyland Ltd., Chennai-Oil change period every 24000 Kms.

### CHARACTERISTICS

| SAE GRADE                       | ALT 140 |
|---------------------------------|---------|
| Kinematic Viscosity cSt @ 100°C | 28-34   |
| Viscosity Index, Min.           | 90      |
| Flash point (COC), °C Min.      | 190     |
| Pour Point, °C Max.             | 0       |

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) OR [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

