

SERVOKOOL ST

GRADES AVAILABLE - SERVOKOOL ST

DESCRIPTION

Servokool ST is a triple action long life radiator coolant prepared from selected ingredients to meet the highest Japanese standard and is free from Amines, Borates, Nitrates and Silicates and Phosphates.

PERFORMANCE BENEFITS

- Does not boil and vaporise in the hottest summer or freeze in severe winter.
- Prevents corrosion of radiator components and other parts.
- Increases cooling efficiency.
- Reduces maintenance costs and increases radiator life.

APPLICATION

Servokool ST is recommended for passenger cars, light commercial vehicles, heavy vehicles and heavy earth moving equipment as a radiator coolant. For desired performance 30 parts of the fluid is to be diluted with 70 parts of distilled water in most of the vehicles.

PERFORMANCE STANDARDS

- JIS K 2234-1994 CLASS 2

CHARACTERISTICS

Appearance	Blue clear liquid
Specific Gravity @ 20°C, Min.	1.114
Boiling Point, °C, Min	155
Freezing Point, °C	
30% Volume Solution	(-) 14
50% Volume Solution	(-) 34
pH of 30 v/v % Soln in distilled water	7.5 – 9.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in