

SERVO PREMIUM ALT 15W-40

GRADES AVAILABLE - SERVO PREMIUM ALT 15W-40

DESCRIPTION

Servo Premium ALT 15W-40 is a premium quality commercial diesel engine oil. The oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines in the over the road transport fleet applications and also off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.

APPLICATION

Servo Premium ALT 15W-40 is recommended for Ashok Leyland commercial vehicles complying with Bharat Stage-I Emission Norms. It is also suitable for earlier models.

PERFORMANCE STANDARDS

- * API CF4
- * MB 228.1

Servo Premium ALT 15W-40 is approved by:

- * Ashok Leyland Ltd, Chennai.

CHARACTERISTICS

SAE GRADE	ALT 15W-40
Kinematic Viscosity, cSt @ 100°C	14.0 – 15.0
Viscosity Index, Min.	135
TBN, mg KOH/g	8.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

